

Easy-1522P/ 2015P Economic type ultrasonic welder

- **Square column adopted**
100x150mm square column is adopted. Deflection during downward stroke is eased and the welding is more stable.
- **Welding depth controlled**
Stopper (screw) is added to control the welding depth. Horn is stopped when the screw is touched. This helps to control the height of welded part even the set WELD TIME is too long.
- **Safety of operator raised**
2 Start buttons are adopted to make sure the horn moves downward only when 2 start buttons are both pressed.
- **Precise of Height adjustment**
Dove-tale design is adopted. Height of machine is adjusted by handwheel .



Specifications:

Frequency	15kHz	20kHz
Max. Output	2600W/ 3200w	1500W/ 2600W
Power supply	220V/ 50Hz/ 10A/ 1P	220V/ 50Hz/ 10A/ 1P
Drive cylinder	Ø63mm air cylinder	Ø63mm air cylinder
Operating mode	Time mode	Time mode
Switches	2 Start buttons and Emergency Stop on the front of base. External start switches is allowed	2 Start buttons and Emergency Stop on the front of base. External start switches is allowed
Dimensions	650x415x1180mm	650x415x1180mm
Weight	125kg (generator included)	125kg (generator included)
Dimensions of generator	560x415x100mm	560x415x100mm